SPEEDY A4 SINGLE-FUNCTION COLOUR LASER PRINTER FOR ENHANCED PRODUCTIVITY

i-SENSYS LBP673Cdw II

Single-function A4 colour devices for smooth and speedy printing processes, designed for ease of use in smaller workspaces.



HIGH-QUALITY PRINTING

Produce high-quality output from toners with a wide range of colours and achieve bright, vibrant prints with excellent reproduction of both light and dark tones in high print quality.

SMOOTH USER EXPERIENCE

Easily carry out a range of print tasks and quickly reach relevant parts of the online manual via a QR code.

360-DEGREE SECURITY

A Security Settings Navigator recommends appropriate security settings to protect against security leaks and cyber threats.

IMPROVE SUSTAINABILITY EFFORTS

Increase your sustainability efforts by embracing devices that use recycled plastic and cardboard packaging for toner cartridges.

Canon

TECHNICAL SPECIFICATIONS

i-SENSYS LBP673Cdw II

PRINTER ENGINE	
Print speed	Single sided : Up to 33 ppm (A4)
	Up to 60 ppm(A5-Landscape) Double sided : Up to 29.5 ipm (A4)
Printing method	Colour laser beam printing
Print quality	Up to 1200 x 1200 dpi
Warm-up time	Approx. 16.6 seconds or less from power on
Print margins	5 mm-top, bottom, left and right
Advanced printing features	Encrypted Secure Print Secure Print Print from USB memory key (JPEG/TIFF/PDF) Microsoft Universal Print support iOS: AirPrint, Canon PRINT app Android; Mopria certified, Canon Print Service Plug-in, Canon PRINT app, IPP everywhere
MEDIA HANDLING	
Paper input (Standard)	250 sheets 50 sheets multi-purpose tray
Paper input (Option)	550 sheets cassette
Maximum paper input capacity	850 sheets
Paper output	150 sheets
Media types	Plain paper, Recycled paper, Heavy Paper, Thin paper, Colour paper, Coated paper, Pre-punched, Label, Post card, Envelope
Media sizes	Cassette (Standard): A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Envelop (COM10, DL, C5, Monarch), Custom sizes: Min. 98 x 148 mm Max. 216.0 x 356.0 mm. Multi-purpose tray:
	A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Indexcard, Envelope (COM10, DL, C5, Monarch), Custom sizes: Min 76 x 127 mm Max. 216.0 x 356.0 mm. Cassette (Optional):
	A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Custom sizes: Min. 100 x 148 mm Max. 216.0 x 356.0 mm.
Media weights	Cassette (standard and optional): 60 to 163 g/m² (Up to 200 g/m² with Coated paper) Multi-purpose tray: 60 to 176 g/m² (Up to 200 g/m² with Coated paper)
Double sided printing	Automatic Cassette: A4, A5, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K Custom size - Min. 148 x 148 mm Max. 216.0 x 356.0 mm 60 to 200 g/m ²
	GENERAL FEATURES
	220-240V (±10%) 50/60Hz (±2Hz)

Power consumption	Maximum: Approx. 1,380W or less Active printing: Approx. 700 W Standby: Approx. 24.0W or less Sleep: Approx. 1.0 W or less Typical Electricity Consumption (TEC): 0.31 kWh/week ⁶ For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/For_Work/ Lot26/index.aspx
Noise level	Sound power ¹ Active: 65dB or less Standby: 36dB or less Sound pressure ¹
	Active: Simplex 51dB (CL)) / 50 dB (BW) Duplex 51dB (CL) / 50dB (BW) Standby: 25 dB
Dimensions (W x D x H)	425 mm x 427 mm x 300 mm
Weight	Approx. 17.1 kg
Operating environment	Temperature: 10 to 30°C (50 to 86°F) Humidity 20 to 80% RH (no condensation)
Control panel	5 Line LCD, 3 LED (Job, Error, Energy saver), Buttons, 10-key numeric keypad
CONTROLLER	
Processor Speed	1200MHz
Memory	1GB
Storage	4GB
Printer Languages	UFRII, PCL5c², PCL6, Adobe® PostScript3
Fonts	45 PCL fonts, 136 PS fonts
Interface and connectivity	USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection
Network Protocol	Print: TCP/IP (LPD/Port9100/IPP/IPPS/WSD) Management: SNMPv1, SNMPv3 (IPv4,IPv6)
	Security: TLS1.3, IPSec, IP/Mac address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS)
	Security (wireless): Infrastructure Mode: WPA-PSK(AES), WPA2-PSK(AES), WPA3-SAE (AES), WPA-EAP(AES), WPA2-EAP(AES), WPA3-EAP(AES) Access Point Mode: WPA2-PSK(AES), WPA3-SAE (AES)
Software and Printer Management	Remote User Interface (RUI), Department ID Management, Toner Status Tool, iW Enterprise Management Console: Server-based software for centralised management of a fleet of devices Cooperating with External Security Audit System (Security Information and Event Management) eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics.



TECHNICAL SPECIFICATIONS

i-SENSYS LBP673Cdw II

Operating Systems Compatibility

Windows® 11 / Windows® 10 / Server® 2025 / Server® 2022 / Server® 2019 / Server® 2016 Mac OS X version 10.15 & up

Linux³

CONSUMABLES

All-in-One cartridges

Cartridge 069 Black (2,100 pages 4)5 Cartridge 069H Black (7,600 pages 4)5 Cartridge 069 Cyan (1,900 pages 4)⁵ Cartridge 069H Cyan (5,500 pages 4)⁵ Cartridge 069 Magenta (1,900 pages ⁴)⁵ Cartridge 069H Magenta (5,500 pages ⁴)⁵ Cartridge 069 Yellow (1,900 pages 4)5 Cartridge 069H Yellow (5,500 pages 4)5

ACCESSORIES/ OPTIONS

PAPER FEEDER PF-K1 (550-sheet cassette) Items

Declared noise emission in accordance with ISO 7779. Based on ISO9296, below figure is different. Active: 62dB or less

[2] Commands supported only. Third party driver or direct printing from application reauired.

Web distribution onlyBased on ISO/IEC 19798

© Printer ships with Black: 1.200 pages, C/M/Y: 1,100 pages starter cartridges

© As per US ENERGY STAR® version3.2



i-SENSYS LBP673Cdw II

Canon Ireland 3006 Lake Drive Citywest, Saggart Co. Dublin, Ireland Telephone No: 01 2052400 Facsimile No: 01 2052525

canon.ie

Canon (UK) Ltd
The Bower
4 Roundwood Avenue
Stockley Park
Uxbridge
UB11 1AF

Canon Inc. Canon.com

Canon Europe canon-europe.com

English Edition © Canon Europa N.V. 2025

